

Claims

1. A guide for guiding a first drill and a second drill while boring a door with holes for receiving a lock, the guide comprising:

- a first element for guiding the first drill and abutting a first face of the door;
- a second element for guiding the first drill and abutting a second face of the door;
- a third element for abutting a side of the door;
- a first threaded bolt connected between the first element and the third element so that the first element is movable on the first face of the door, the first threaded bolt being operable for driving the first element against the first face of the door; and
- a second threaded bolt being connected between the second element and the third element so that the second element is movable on the second face of the door, the second threaded bolt being operable for driving the second element against the second face of the door.

2. The guide according to claim 1 wherein the first element defines a window for receiving the first drill.

3. The guide according to claim 2 wherein the first element comprises a rim extending around the window for guiding the first drill.

4. The guide according to claim 1 wherein the second element defines a window for receiving the first drill.

5. The guide according to claim 4 wherein the second element comprises a rim extending around the window for guiding the first drill.

6. The guide according to claim 1 wherein the third element defines a

- 1 window for receiving the second drill.
- 2 7. The guide according to claim 6 wherein the third element comprises a
3 rim extending around the window for guiding the second drill.
- 4 8. The guide according to claim 1 wherein the center of the window of
5 the third element is movable between an aligned position and a
6 non-aligned position relative to the middle of the side of the door.
- 7 9. The guide according to claim 1 wherein the third element comprises a
8 first portion connected with the first threaded bolt, a second portion
9 connected with the second threaded bolt and a third portion formed
10 between the first portion and the second portion.
- 11 10. The guide according to claim 9 wherein the third element further
12 includes a threaded hole defined in the first portion thereof for
13 receiving the first threaded bolt.
- 14 11. The guide according to claim 10 wherein the first element defines two
15 holes for receiving the first threaded bolt.
- 16 12. The guide according to claim 10 wherein the first element defines a
17 slot for receiving the first threaded bolt.
- 18 13. The guide according to claim 9 wherein the third element includes a
19 threaded hole defined in the second portion thereof for receiving the
20 second threaded bolt.
- 21 14. The guide according to claim 13 wherein the second element defines
22 two holes for receiving the second threaded bolt.
- 23 15. The guide according to claim 13 wherein the second element defines
24 a slot for receiving the second threaded bolt.
- 25 16. The guide according to claim 1 wherein the third element is
26 sandwiched between first element and the second element.

1 17. The guide according to claim 16 wherein the first element comprises
2 a bracket for receiving the third element.

3 18. The guide according to claim 16 wherein the second element
4 comprises a bracket for receiving the third element.

5

6